

FLAIRMO AIR DRYER RAD 200

More about the FLAIRMO Air Dryer RAD 200

The refrigerated air dryers from FL AIR MO have incorporated several unique design features to give a long lifetime with minimum and easy maintenance. The compact dryers give you an efficient drying with low pressure drop and it will give the air system a longer lifetime

- State of the art design ensures a constant 3°C pressure dew point.
- High efficiency stainless steel heat exchanger.
- Environmentally ozone friendly R134a and R407C refrigerant.
- Conforms to stringent ISO8573-1 standards.

Specifications

Outlet Pressure Dew Point Of 3°C	200 l/min
Outlet Pressure Dew Point Of 7°C	250 l/min
Outlet Pressure Dew Point Of 10°C	280 l/min
Inlet Air Temperature	5 - 50 °C
Inlet Air Pressure Min - Max	1.5 - 10 Bar
Ambient Operating Temp.	2 - 40 °C
Power Source	230 V
Current	1.2 Amp
Power Consumption	180 W
Circuit Breaker	5 Amp
Noise Level	50 dB(A) / 1 m
Connection	3/8 Inch
Min. Service Interval	12 Months
Drain	Float
LxWxH	410 x 226 x 473 mm
Weight	18 kg

FLAIRMO

Call us on +45 53 71 72 20
or visit flairmo.dk